



CHRYSMETAL OOD

BVALVE

**СПИРАТЕЛНИ ВЕНТИЛИ СЪС СИЛФОННО
УПЛЪТНЕНИЕ НА ФЛАНЦИ BVALVE ИСПАНИЯ**
FLANGED BELLOWS SEALED GLOBE VALVES BVALVE SPAIN



	PN16	PN25	PN40
Тип Type	BV25061	BV25063	BV25065
Тяло Body	EN-JL 1040	EN-GJS-400-18-LT	WCB 1.0619
Tmax	-10°C + 300°C	-10°C + 350°C	-10°C + 400°C
Размер Size DN	Код Code	Код Code	Код Code
15	203004	203104	203204
20	203005	203105	203205
25	203006	203106	203206
32	203007	203107	203207
40	203008	203108	203208
50	203009	203109	203209
65	203010	203110	203210
80	203011	203111	203211
100	203012	203112	203212
125	203013	203113	203213
150	203014	203114	203214
200	203015	203115	203215
250	203016		203216
300	203017		203217

Работни условия - Working conditions for type BV25061

Temperature °C	-10/120	150	200	250	300
Pressure Bar	16	14,40	12,80	11,20	9,60

Работни условия - Working conditions for type BV25063

Temperature °C	-10/120	150	200	250	300	350
Pressure Bar	25	24,30	23	21,80	20	17,50

Работни условия - Working conditions for type BV25065

Temperature °C	-10/120	150	200	250	300	350	400
Pressure Bar	40	35,20	33,30	30,40	27,60	25,70	23,80