

ИЗОЛАЦИОННИ ТРЪБИ INSULATION TUBES



КРИСМЕТАЛ ООД

		RUBAFLEX	EUROBATEX
Коефициент на топлопроводимост <i>Thermal conductivity λ</i>	0°C	0,036w/mk	0,033w/mk
	40°C	0,040w/mk	0,039w/mk
Работна температура <i>Working temperature</i>		-45°C ÷ +115°C	-45°C ÷ +105°C
Пожароопасност - <i>Fire rating</i>		M1-NF, Class 1 BS476/UNI	
Устойчивост на преминаване на водни изпарения <i>Water vapor diffusion resist μ</i>		≥5000 EN12086 (DIN52615)	≥7000 EN12086 (DIN52615)
		320xxx	321xxx
Екологични характеристики <i>Environmental characteristics</i>		CFC, HCFC free	
		Formaldehyd free	O.D.P. zero

Rubaflex



Тип - Type	RUBAFLEX 13mm	EUROBATEX 13mm
Дебелина х вътр. D <i>Thk x Int. Dia. (mm)</i>	Код <i>Code</i>	Код <i>Code</i>
13 x 10	320710	321810
13 x 12	320712	321812
13 x 15	320715	321814(x14)
13 x 18	320718	321818
13 x 22	320722	321822
13 x 27	320727	321827
13 x 34	320734	321834
13 x 43	320743	321842
13 x 48	320749	321848
13 x 54	320754	321854
13 x 60	320761	321860
13 x 64	320764	321864
13 x 76	320777	321876
13 x 90	320791	321890
13 x 108	320796	321892
13 x 114	320797	321893
13 x 139	320798	321896



Тип - Type	RUBAFLEX 19mm	RUBAFLEX 19 mm
Дебелина х вътр. D <i>Thk x Int. Dia. (mm)</i>	Код <i>Code</i>	Код <i>Code</i>
19 x 18	320918	321918
19 x 22	320922	321922
19 x 27	320927	321927
19 x 34	320934	321934
19 x 43	320943	321942
19 x 48	320949	321948
19 x 54	320954	321954
19 x 60	320961	321960
19 x 77	320977	321976
19 x 90	320991	321990
19 x 101	320995	321991
19 x 114	320997	321993
19 x 139	320998	321996